

View Online at <https://aerobasegroup.com/nsn/5950-00-432-9281>

Reliability Indicator:

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

1.750 inches 1.750 inches

Body Width:

0.812 inches 0.812 inches

Body Height:

1.750 inches 1.750 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

1 single group1 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

6.0 milliamperes dc single component single secondary and 16.0 milliamperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Special Features:

Secondary voltage and current have been rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0