

View Online at <https://aerobasegroup.com/nsn/5950-00-433-1373>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 0.780 inches and 0.840 inches

Body Outside Diameter:

Between 0.980 inches and 1.020 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.090 inches single mounting facility single center group and 1.150 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

4.0 amperes ac single component single primary

Winding Power Rating:

0.005 volts-amperes single component single secondary

Winding Operating Voltage:

5.00 dc volts single component single secondary

Test Data Document:

88818-g146-629 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0