

View Online at <https://aerobasegroup.com/nsn/5950-00-433-1373>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

Between 0.780 inches and 0.840 inches

**Body Outside Diameter:**

Between 0.980 inches and 1.020 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.090 inches single mounting facility single center group and 1.150 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

4.0 amperes ac single component single primary

**Winding Power Rating:**

0.005 volts-amperes single component single secondary

**Winding Operating Voltage:**

5.00 dc volts single component single secondary

**Test Data Document:**

88818-g146-629 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0