## NSN 5950-00-433-2444

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-433-2444

#### **Reliability Indicator:**

Not establishednot established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.820 inches single mounting facility single center group and 1.820 inches single mounting facility single center group and 1.840 inches single mounting facility single center group and 1.840 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.240 inches single mounting facility single center group and 1.240 inches single mounting facility single center group and 1.260 inches single mounting facility single center group and 1.260 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

2.660 inches 2.660 inches

#### **Body Width:**

2.120 inches 2.120 inches

#### **Body Height:**

2.300 inches 2.300 inches

#### **Maximum Operating Temp:**

105.0 degrees celsius105.0 degrees celsius

## Inclosure Type:

Fully enclosedfully enclosed

#### **Mounting Facility Quantity:**

4 single group4 single group

#### **Mounting Method:**

Threaded hole single groupthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

#### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

1.0 amperes ac single component 2nd secondary

#### Winding Operating Voltage:

6.30 ac volts single component 2nd secondary28.00 ac volts single component 1st secondary

#### **Test Data Document:**

80063-sm-d-2018649 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

6 tab, solder lug

#### Shelf Life:

N/a

#### **Unit Of Measure:**

# NSN 5950-00-433-2444

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0