NSN 5950-00-433-6049

Power Transformer - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-433-6049

| 1.300 inches Frequency Rating: 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Vortage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: N/a | Overall Height: | | | | | |
|---|---|--|--|--|--|--|
| 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility Single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Current: 3.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 1.300 inches | | | | | |
| Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary 115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Frequency Rating: | | | | | |
| Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 380.0 hertz single component and 420.0 hertz single component | | | | | |
| Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility Single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Input-output Phase Relationship: | | | | | |
| Internal shield brought out to terminal single component Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Single phase to single phase single component | | | | | |
| Body Length: 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Shielding Method: | | | | | |
| 1.400 inches Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Internal shield brought out to terminal single component | | | | | |
| Body Width: 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Body Length: | | | | | |
| 1.200 inches Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single component single secondary Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 1.400 inches | | | | | |
| Body Height: 1.100 inches Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Body Width: | | | | | |
| Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 1.200 inches | | | | | |
| Maximum Operating Temp: 125.0 degrees celsius Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Body Height: | | | | | |
| Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 1.100 inches | | | | | |
| Distance Between Mounting Facility Centers: 1.000 inches single mounting facility single center group Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Maximum Operating Temp: | | | | | |
| Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 125.0 degrees celsius | | | | | |
| Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Distance Between Mounting Facility Centers: | | | | | |
| Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 1.000 inches single mounting facility single center group | | | | | |
| Mounting Facility Quantity: 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Inclosure Type: | | | | | |
| 2 single group Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Fully enclosed | | | | | |
| Mounting Method: Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Mounting Facility Quantity: | | | | | |
| Threaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | 2 single group | | | | | |
| Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Mounting Method: | | | | | |
| 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | | | | | | |
| Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Threaded hole single group | | | | | |
| Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | | | | | | |
| Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: | | | | | |
| 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component | | | | | |
| Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): | | | | | |
| 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group | | | | | |
| Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: | | | | | |
| 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group | | | | | |
| Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: | | | | | |
| Unc single group Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary | | | | | |
| Terminal Type And Quantity: 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: | | | | | |
| 5 solder stud Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary | | | | | |
| Shelf Life: | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: | | | | | |
| | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group | | | | | |
| N/a | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: | | | | | |
| | Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 8.35 ac volts single component single secondary115.00 ac volts single component single primary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 solder stud | | | | | |

NSN 5950-00-433-6049

Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0