# NSN 5950-00-433-6196

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-433-6196

## **Reliability Indicator:**

Not establishednot established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.938 inches single mounting facility single center group0.938 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

## Frequency Rating:

400.0 hertz single component400.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Body Length:

1.250 inches 1.250 inches

#### Body Width:

0.880 inches 0.880 inches

#### Body Height:

1.190 inches 1.190 inches

## Inclosure Type:

Fully enclosedfully enclosed

## Mounting Facility Quantity:

4 single group4 single group

# Mounting Method:

Threaded hole single groupthreaded hole single group

# Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thready Qty Per Inch (tpi):

40 single group40 single group

# Thread Size:

0.112 inches single group0.112 inches single group

# Winding Operating Current:

214.0 milliamperes ac single component single secondary

# Winding Operating Voltage:

28.00 ac volts single component single secondary115.00 ac volts single component single primary

# Thread Series Designator:

Unc single group

# Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5950-00-433-6196

Power Transformer - Page 2 of 2

**Fiig:** A058b0

