NSN 5950-00-433-7192

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-433-7192

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.720 inches single mounting facility single center group and 2.720 inches single mounting facility single center group and 2.780 inches single mounting facility single center group and 2.780 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.940 inches single mounting facility single center group and 1.940 inches single mounting facility single center group and 2.060 inches single mounting facility single center group and 2.060 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component and three phase to six phase single component and three phase to three phase single component componentthree phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-delta and delta-wyedelta-wye

Winding Shielding Method:

Grounded to inclosure and brought out to terminal single componentgrounded to inclosure and brought out to terminal single component

Body Length:

3.880 inches 3.880 inches

Body Width:

2.880 inches 2.880 inches

Body Height:

2.120 inches 2.120 inches

Maximum Operating Temp:

170.0 degrees celsius170.0 degrees celsius

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

4.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

14.40 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 turret

Shelf Life:

. . .

NSN 5950-00-433-7192

Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0