NSN 5950-00-434-2889

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-434-2889
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches single mounting facility single center group
Mounting Hole Diameter:
0.250 inches single group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.620 inches
Body Width:
2.120 inches
Body Height:
3.120 inches
Inclosure Type:
Fully enclosed
Fully enclosed Mounting Facility Quantity:
•
Mounting Facility Quantity:
Mounting Facility Quantity: 4 single group
Mounting Facility Quantity: 4 single group Mounting Method:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity: 10 tab, solder lug
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity: 10 tab, solder lug Shelf Life:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Winding Operating Voltage: 115.00 ac volts single component single primary Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:

A058b0