NSN 5950-00-434-3093Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-434-3093
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.675 inches single mounting facility single center group and 1.685 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.435 inches single mounting facility single center group and 1.445 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
2.310 inches
Body Width:
2.060 inches
Body Height:
3.120 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
500.0 milliamperes ac single component single secondary
Winding Operating Voltage:
90.00 ac volts single component single secondary115.00 ac volts single component single primary
Test Data Document:
97942-128c943 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-00-434-3093

Power Transformer - Page 2 of 2



Fiig:

A058b0