

View Online at <https://aerobasegroup.com/nsn/5950-00-434-4355>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.480 inches single mounting facility single center group and 2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group2.520 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.980 inches single mounting facility single center group and 1.980 inches single mounting facility single center group and 2.020 inches single mounting facility single center group2.020 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group0.188 inches single group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 2.980 inches and 2.980 inches and 3.020 inches 3.020 inches

Body Width:

Between 2.480 inches and 2.480 inches and 2.520 inches 2.520 inches

Body Height:

2.160 inches 2.160 inches

Maximum Operating Temp:

180.0 degrees fahrenheit180.0 degrees fahrenheit

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Voltage:

117.00 ac volts single component single primary60.00 ac volts single component single secondary and 66.00 ac volts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0