

View Online at <https://aerobasegroup.com/nsn/5950-00-434-9080>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded and brought out to terminal single component and internal shield brought out to terminal single component

Body Length:

Between 1.110 inches and 1.140 inches

Body Width:

Between 0.844 inches and 0.875 inches

Body Height:

Between 0.899 inches and 0.930 inches

Distance Between Mounting Facility Centers:

0.750 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Operating Current:

20.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

20.00 ac volts single component 1st secondary 22.50 ac volts single component single primary and 115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0