

View Online at <https://aerobasegroup.com/nsn/5950-00-436-6267>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.985 inches single mounting facility single center group and 1.015 inches single mounting facility single center group

**Overall Height:**

2.000 inches

**Mounting Hole Diameter:**

0.151 inches single group and 0.161 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

1.750 inches

**Body Width:**

1.375 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Operating Current:**

250.0 milliamperes ac single component all secondary

**Winding Power Rating:**

4.7 volts-amperes single component 2nd secondary

**Winding Operating Voltage:**

58.30 ac pounds per hour wet single component 1st secondary

**Test Data Document:**

10001-2661896 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0