

View Online at <https://aerobasegroup.com/nsn/5950-00-436-6282>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.485 inches single mounting facility single center group and 1.515 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.110 inches single mounting facility single center group and 1.140 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.030 inches

Body Width:

1.750 inches

Body Height:

1.530 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 milliamperes ac single component all secondary

Winding Power Rating:

1.15 volts-amperes single component all secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Test Data Document:

10001-2682940 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0