# NSN 5950-00-436-6282

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-436-6282

# Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.485 inches single mounting facility single center group and 1.515 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.110 inches single mounting facility single center group and 1.140 inches single mounting facility single center group

## Frequency Rating:

60.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.030 inches

Body Width:

1.750 inches

Body Height:

1.530 inches

### Maximum Operating Temp:

130.0 degrees celsius

#### Inclosure Type:

Fully enclosed

### Mounting Facility Quantity:

4 single group

### Mounting Method:

Threaded hole single group

### Winding Function And Quantity:

1 primary single component and 2 secondary single component

## Thread Size:

0.138 inches single group

### Winding Operating Current:

10.0 milliamperes ac single component all secondary

### Winding Power Rating:

1.15 volts-amperes single component all secondary

### Winding Operating Voltage:

115.00 ac volts single component single primary

### Test Data Document:

10001-2682940 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

6 turret

#### Shelf Life:

N/a

# NSN 5950-00-436-6282

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

