

View Online at <https://aerobasegroup.com/nsn/5950-00-436-7817>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.210 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.984 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.900 inches

Body Width:

1.600 inches

Body Height:

1.650 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

420.0 milliamperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary 10.20 ac volts single component single secondary and 26.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0