

View Online at <https://aerobasegroup.com/nsn/5950-00-437-3762>

Reliability Indicator:

Not established

Overall Length:

Between 5.090 inches and 5.150 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.610 inches single mounting facility single center group and 4.640 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.110 inches single mounting facility single center group and 1.140 inches single mounting facility single center group

Overall Height:

3.000 inches

Mounting Hole Diameter:

0.178 inches single group and 0.183 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to core and brought out to terminal single component

Body Width:

1.750 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

900.0 milliamperes ac single component all secondary

Winding Operating Voltage:

42.00 ac volts single component all secondary

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0