NSN 5950-00-439-5763

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-439-5763

Reliability Indicator:Not establishedCenter To Center Distance Between Mounting Facilities Parallel To Length:2.500 inches single mounting facility single center groupCenter To Center Distance Between Mounting Facilities Parallel To Width:1.500 inches single mounting facility single center groupFrequency Rating:400.0 hertz single componentInput-output Phase Relationship:Single phase to single phase single componentWinding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.750 inches

Body Width:

2.000 inches

Body Height:

1.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

117.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

20.0 volts-amperes single component 2nd secondary0.01 volts-amperes single component 1st secondary

Winding Operating Voltage:

85.00 ac volts single component 3rd secondary52.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

NSN 5950-00-439-5763

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

