NSN 5950-00-441-7876

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-441-7876

Reliability Indicator:

Not establishednot established

Overall Length:

1.312 inches 1.312 inches

Overall Width:

1.312 inches 1.312 inches

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Height:

1.750 inches 1.750 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Distance Between Mounting Facility Centers:

0.375 inches single mounting facility single center group0.375 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

600.0 milliamperes ac single component all secondary

Winding Power Rating:

31.8 volts-amperes single component all secondary31.8 volts-amperes single component all secondary

Winding Operating Voltage:

115.00 ac volts single component single primary 6.00 ac volts single component all secondary and 6.00 ac volts single component all

secondary and 53.00 ac volts single component all secondary 53.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-00-441-7876

Power Transformer - Page 2 of 2

Fiig: A058b0

