# NSN 5950-00-442-2113

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-442-2113

### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

#### **Overall Height:**

4.875 inches

#### **Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-wye

#### Winding Shielding Method:

#### Internal shield brought out to terminal single component

**Body Length:** 

5.750 inches

#### **Body Width:**

4.450 inches

#### Maximum Operating Temp:

70.0 degrees celsius

#### Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

#### Winding Function And Quantity:

3 primary single component and 2 secondary single component

#### Thread Size:

0.250 inches single group

# Winding Operating Current:

9.9 amperes ac single component all secondary

# Winding Operating Voltage:

213.00 ac volts single component 1st primary25.30 ac volts single component all secondary204.00 ac volts single component 3rd

primary208.00 ac volts single component 2nd primary

## **Thread Series Designator:**

Unc single group

# Terminal Type And Quantity:

6 threaded stud and 13 turret

# Shelf Life:

# NSN 5950-00-442-2113

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

