

View Online at <https://aerobasegroup.com/nsn/5950-00-442-9453>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.312 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.360 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.700 inches

Body Width:

2.670 inches

Body Height:

2.150 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 milliamperes ac single component single secondary

Winding Operating Voltage:

3.21 ac kilovolts single component single secondary 113.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0