

View Online at <https://aerobasegroup.com/nsn/5950-00-443-1796>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches all mounting facilities all center groupings2.125 inches all mounting facilities all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches all mounting facilities all center groupings1.750 inches all mounting facilities all center groupings

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Body Length:

Between 2.745 inches and 2.745 inches and 2.755 inches 2.755 inches

Body Width:

Between 2.375 inches and 2.375 inches and 2.385 inches 2.385 inches

Body Height:

Between 2.805 inches and 2.805 inches and 2.815 inches 2.815 inches

Maximum Operating Temp:

105.0 degrees celsius105.0 degrees celsius

Inclosure Type:

Hermetically sealed with oilhermetically sealed with oil

Mounting Facility Quantity:

4 all groupings4 all groupings

Mounting Method:

Threaded stud 1st groupthreaded stud 1st group

Thread Size:

0.138 inches all groupings0.138 inches all groupings

Winding Operating Current:

0.03 amperes ac single component single primary

Winding Operating Voltage:

103.00 ac volts single component single primary and 103.00 ac volts single component single primary and 127.00 ac volts single component single primary127.00 ac volts single component single primary

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0