

View Online at <https://aerobasegroup.com/nsn/5950-00-443-9306>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches single mounting facility single center group6.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.812 inches single mounting facility single center group2.812 inches single mounting facility single center group

**Frequency Rating:**

45.0 hertz single component and 45.0 hertz single component and 440.0 hertz single component440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

7.125 inches 7.125 inches

**Body Width:**

3.438 inches 3.438 inches

**Body Height:**

2.938 inches 2.938 inches

**Inclosure Type:**

Partially enclosed, double shellpartially enclosed, double shell

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Voltage:**

118.00 ac volts single component single primary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0