

View Online at <https://aerobasegroup.com/nsn/5950-00-443-9306>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.812 inches single mounting facility single center group2.812 inches single mounting facility single center group

Frequency Rating:

45.0 hertz single component and 45.0 hertz single component and 440.0 hertz single component440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

7.125 inches 7.125 inches

Body Width:

3.438 inches 3.438 inches

Body Height:

2.938 inches 2.938 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Voltage:

118.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0