

View Online at <https://aerobasegroup.com/nsn/5950-00-444-0352>

Reliability Indicator:

Not establishednot establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group0.188 inches single group0.188 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single componentthree phase to three phase single component

Transformer Winding Connection Type:

Wye-wyewye-wyewye-wye

Body Length:

2.250 inches 2.250 inches 2.250 inches

Body Width:

1.500 inches 1.500 inches 1.500 inches

Body Height:

2.625 inches 2.625 inches 2.625 inches

Maximum Operating Temp:

70.0 degrees celsius70.0 degrees celsius70.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: