

View Online at <https://aerobasegroup.com/nsn/5950-00-444-3629>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.125 inches single group0.125 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

Body Length:

1.690 inches 1.690 inches

Body Width:

0.950 inches 0.950 inches

Body Height:

0.880 inches 0.880 inches

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.380 inches single mounting facility single center group1.380 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Winding Operating Current:

40.0 milliamperes ac single component all secondary

Winding Operating Voltage:

7.00 ac volts single component 1st secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0