# NSN 5950-00-444-3944

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-444-3944

#### Reliability Indicator:

Not established

#### Overall Length:

2.750 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.360 inches single mounting facility single center group and 1.390 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.230 inches single mounting facility single center group and 1.270 inches single mounting facility single center group

**Overall Height:** 

1.937 inches

Overall Width:

1.812 inches

#### Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

#### Inclosure Type:

Hermetically sealed

# Mounting Facility Quantity:

4 single group

# Mounting Method:

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 3 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

# Winding Operating Current:

1.4 amperes ac single component 2nd secondary

# Winding Operating Voltage:

6.30 ac volts single component all secondary114.00 ac volts single component single primary

# Thread Series Designator:

Unc single group

# Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5950-00-444-3944

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

