

View Online at <https://aerobasegroup.com/nsn/5950-00-445-3312>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.391 inches single mounting facility single center group and 3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.453 inches single mounting facility single center group and 2.547 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.625 inches

Body Width:

3.469 inches

Body Height:

5.469 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

18.5 amperes ac single component single secondary

Winding Operating Voltage:

104.00 ac volts single component single primary and 6.60 ac volts single component single secondary 109.00 ac volts single component single primary and 115.00 ac volts single component single primary and 121.00 ac volts single component single primary and 127.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0