NSN 5950-00-446-6087

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-446-6087

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.875 inches single mounting facility single center group |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.750 inches single mounting facility single center group |
| Impedance Rating In Ohms: |
| 50.0 single component single primary |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 3.660 inches |
| Body Width: |
| 1.680 inches |
| Body Height: |
| 3.680 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |

A058b0