

View Online at <https://aerobasegroup.com/nsn/5950-00-448-0670>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.063 inches single mounting facility single center group3.063 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

4.000 inches 4.000 inches

Body Width:

4.680 inches 4.680 inches

Body Height:

6.000 inches 6.000 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

20 single group20 single group

Thread Size:

0.250 inches single group0.250 inches single group

Winding Operating Current:

80.0 milliamperes ac single component single secondary

Winding Operating Voltage:

105.00 ac volts single component single primary and 110.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0