## NSN 5950-00-450-2281

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-450-2281

| Reliability Indicator:  |
|---|
| Not established   |
|   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.875 inches single mounting facility single center group                 |
| Overall Height:   |
| 2.875 inches  |
| Overall Width:  |
| 2.625 inches  |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Three phase to six phase single component                                 |
| Winding Shielding Method:   |
| Internal shield brought out to terminal single component                  |
| Body Length:  |
| 4.000 inches  |
| Body Width:   |
| 2.375 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 5 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.190 inches single group   |
| Thread Series Designator:   |
| Unf single group  |
| Terminal Type And Quantity:   |
| 18 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-00-450-2281

Power Transformer - Page 2 of 2



Fiig:

A058b0