

View Online at <https://aerobasegroup.com/nsn/5950-00-450-2348>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

2.250 inches 2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches single mounting facility single center group1.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.500 inches single mounting facility single center group1.500 inches single mounting facility single center group

**Overall Height:**

2.500 inches 2.500 inches

**Mounting Hole Diameter:**

0.166 inches single group0.166 inches single group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single componentinternal shield grounded to inclosure and core single component

**Body Length:**

1.875 inches 1.875 inches

**Body Width:**

1.875 inches 1.875 inches

**Body Height:**

2.219 inches 2.219 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Winding Operating Current:**

320.0 milliamperes ac single component single secondary

**Winding Power Rating:**

41.6 volts-amperes single component single secondary41.6 volts-amperes single component single secondary

**Winding Operating Voltage:**

418.00 ac volts single component single primary and 418.00 ac volts single component single primary and 440.00 ac volts single component single primary and 440.00 ac volts single component single primary and 462.00 ac volts single component single primary462.00 ac volts single component single primary

**Terminal Type And Quantity:**

6 tab, solder lug6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0