

View Online at <https://aerobasegroup.com/nsn/5950-00-450-2395>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.550 inches single mounting facility single center group and 0.550 inches single mounting facility single center group and 0.570 inches single mounting facility single center group0.570 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.740 inches single mounting facility single center group and 0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group0.760 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.100 inches single group0.100 inches single group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

1.100 inches 1.100 inches

**Body Width:**

0.900 inches 0.900 inches

**Body Height:**

0.840 inches 0.840 inches

**Maximum Operating Temp:**

105.0 degrees celsius105.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Winding Operating Current:**

154.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

26.00 ac volts single component single primary

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0