



View Online at <https://aerobasegroup.com/nsn/5950-00-450-2395>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.550 inches single mounting facility single center group and 0.550 inches single mounting facility single center group and 0.570 inches single mounting facility single center group0.570 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.740 inches single mounting facility single center group and 0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group0.760 inches single mounting facility single center group

Mounting Hole Diameter:

0.100 inches single group0.100 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

1.100 inches 1.100 inches

Body Width:

0.900 inches 0.900 inches

Body Height:

0.840 inches 0.840 inches

Maximum Operating Temp:

105.0 degrees celsius105.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

154.0 milliamperes ac single component single secondary

Winding Operating Voltage:

26.00 ac volts single component single primary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0