

View Online at <https://aerobasegroup.com/nsn/5950-00-450-3435>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Mounting Hole Diameter:

0.165 inches single group and 0.175 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

2.820 inches

Body Width:

2.250 inches

Body Height:

1.160 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

30.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

87.30 ac volts single component 4th secondary and 92.70 ac volts single component 4th secondary

Terminal Type And Quantity:

14 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0