

View Online at <https://aerobasegroup.com/nsn/5950-00-451-2891>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.555 inches single mounting facility single center group and 6.605 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.675 inches single mounting facility single center group and 4.725 inches single mounting facility single center group

**Overall Height:**

5.833 inches

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

8.408 inches

**Body Width:**

7.298 inches

**Body Height:**

5.071 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

18 single group

**Thread Size:**

0.312 inches single group

**Winding Operating Current:**

20.4 amperes ac single component single secondary

**Winding Operating Voltage:**

19.40 ac volts single component single secondary

**Special Features:**

Primary winding taps provided to adjust for minor differences in the source voltage to maintain the output at the specified level

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

21 standoff, solder lug and 3 standoff, threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0