

View Online at <https://aerobasegroup.com/nsn/5950-00-451-2891>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.555 inches single mounting facility single center group and 6.605 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.675 inches single mounting facility single center group and 4.725 inches single mounting facility single center group

Overall Height:

5.833 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

8.408 inches

Body Width:

7.298 inches

Body Height:

5.071 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

20.4 amperes ac single component single secondary

Winding Operating Voltage:

19.40 ac volts single component single secondary

Special Features:

Primary winding taps provided to adjust for minor differences in the source voltage to maintain the output at the specified level

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 standoff, solder lug and 3 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0