

View Online at <https://aerobasegroup.com/nsn/5950-00-451-4216>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.437 inches single mounting facility single center group1.437 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group1.437 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

2.500 inches 2.500 inches

Body Width:

2.312 inches 2.312 inches

Body Height:

2.060 inches 2.060 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

17.0 milliamperes ac single component single secondary

Winding Operating Voltage:

42.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0