

View Online at <https://aerobasegroup.com/nsn/5950-00-453-5568>

**Reliability Indicator:**

Not establishednot establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.953 inches single mounting facility single center group1.953 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.953 inches single mounting facility single center group0.953 inches single mounting facility single center group

**Overall Height:**

4.687 inches 4.687 inches

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

2.750 inches 2.750 inches

**Body Width:**

1.750 inches 1.750 inches

**Body Height:**

4.250 inches 4.250 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Current:**

20.0 amperes ac single component single secondary

**Winding Operating Voltage:**

20.70 ac volts single component single secondary120.00 ac volts single component single primary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

5 eyelet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0