

View Online at <https://aerobasegroup.com/nsn/5950-00-454-8584>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Overall Height:

3.130 inches 3.130 inches

Frequency Rating:

392.0 hertz single component and 392.0 hertz single component and 408.0 hertz single component408.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

1.940 inches 1.940 inches

Body Width:

1.810 inches 1.810 inches

Body Height:

2.750 inches 2.750 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.138 inches single group0.138 inches single group

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

109.00 ac volts single component single primary and 114.00 ac volts single component single primary and 120.00 ac volts single component single primary and 126.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0