

View Online at <https://aerobasegroup.com/nsn/5950-00-455-5985>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Core grounded and brought out to terminal single component

Body Length:

5.750 inches

Body Width:

4.450 inches

Body Height:

4.250 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

3 primary single component and 2 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

18.9 amperes ac single component all secondary

Winding Operating Voltage:

215.00 ac volts single component 1st primary 208.00 ac volts single component 2nd primary 215.00 ac volts single component 1st primary

Special Features:

3primary windings; 2secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 turret and 6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0