

View Online at <https://aerobasegroup.com/nsn/5950-00-455-5987>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.117 inches single mounting facility single center group and 2.137 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.665 inches single mounting facility single center group and 1.685 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.870 inches

Body Width:

2.370 inches

Body Height:

4.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

18.0 amperes ac single component all secondary

Winding Power Rating:

42.12 volts-amperes single component 2nd secondary 28.08 volts-amperes single component 1st secondary

Winding Operating Voltage:

2.34 ac volts single component 2nd secondary 1.56 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0