

View Online at <https://aerobasegroup.com/nsn/5950-00-456-1760>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

Between 3.794 inches and 3.810 inches

**Body Width:**

Between 3.604 inches and 3.620 inches

**Body Height:**

Between 3.234 inches and 3.250 inches

**End Application:**

Wsd: launcher, tubular, f/gm tow wpn sys (m220a1); improved contact support set

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

0.6 amperes dc single component single secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

21.20 dc volts single component single secondary and 69.00 dc volts single component single secondary

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

13 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0