

View Online at <https://aerobasegroup.com/nsn/5950-00-456-1760>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 3.794 inches and 3.810 inches

Body Width:

Between 3.604 inches and 3.620 inches

Body Height:

Between 3.234 inches and 3.250 inches

End Application:

Wsd: launcher, tubular, f/gm tow wpn sys (m220a1); improved contact support set

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

0.6 amperes dc single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

21.20 dc volts single component single secondary and 69.00 dc volts single component single secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

13 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0