

View Online at <https://aerobasegroup.com/nsn/5950-00-456-5936>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.687 inches single mounting facility single center group1.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.437 inches single mounting facility single center group1.437 inches single mounting facility single center group

**Overall Height:**

3.687 inches 3.687 inches

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

**Body Length:**

2.327 inches 2.327 inches

**Body Width:**

2.077 inches 2.077 inches

**Body Height:**

3.250 inches 3.250 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.138 inches single group0.138 inches single group

**Winding Operating Current:**

8.33 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

71.20 ac volts single component 2nd secondary120.00 ac volts single component single primary240.00 ac volts single component 3rd secondary

**Special Features:**

Terminal no. 6 included in two secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0