# NSN 5950-00-456-8441

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-456-8441

_			
R۵	liahi	litv	Indicator:
ĸe	IIabi	IILV	mulcator.

Not establishednot established

#### Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 60.0 hertz single component 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

#### **Body Length:**

3.560 inches 3.560 inches

#### **Body Width:**

3.060 inches 3.060 inches

#### **Body Height:**

3.880 inches 3.880 inches

#### **Inclosure Type:**

Fully enclosedfully enclosed

## **Mounting Facility Quantity:**

4 single group4 single group

## **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group32 single group

# Thread Size:

0.164 inches single group 0.164 inches single group

## **Winding Operating Current:**

1.5 amperes ac single component single secondary

## **Winding Operating Voltage:**

105.00 ac volts single component single primary and 35.00 ac volts single component single secondary115.00 ac volts single component single primary and 125.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

6 standoff, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A058b0