

View Online at <https://aerobasegroup.com/nsn/5950-00-458-5754>

**Reliability Indicator:**

Not establishednot established

**Overall Length:**

4.062 inches 4.062 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.500 inches single mounting facility single center group3.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.188 inches single mounting facility single center group2.188 inches single mounting facility single center group

**Overall Height:**

3.875 inches 3.875 inches

**Overall Width:**

3.375 inches 3.375 inches

**Frequency Rating:**

380.0 hertz single component and 380.0 hertz single component and 1.0 kilohertz single component1.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Maximum Operating Temp:**

130.0 degrees celsius130.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.164 inches single group0.164 inches single group

**Winding Operating Current:**

3.2 amperes ac single component single secondary

**Winding Power Rating:**

400.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

105.00 ac volts single component single secondary and 115.00 ac volts single component single secondary and 125.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0