

View Online at <https://aerobasegroup.com/nsn/5950-00-458-5754>

Reliability Indicator:

Not establishednot established

Overall Length:

4.062 inches 4.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.188 inches single mounting facility single center group2.188 inches single mounting facility single center group

Overall Height:

3.875 inches 3.875 inches

Overall Width:

3.375 inches 3.375 inches

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 1.0 kilohertz single component1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.164 inches single group0.164 inches single group

Winding Operating Current:

3.2 amperes ac single component single secondary

Winding Power Rating:

400.0 volts-amperes single component single secondary

Winding Operating Voltage:

105.00 ac volts single component single secondary and 115.00 ac volts single component single secondary and 125.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0