## NSN 5950-00-458-7484

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-458-7484

Mounting Hole Diameter:  0.138 inches single group Inductance Type: Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inductance Type: Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Mounting Hole Diameter:
Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	0.138 inches single group
Inductance Rating:  25.00 millihenries single component single winding  Body Length:  0.500 inches  Body Outside Diameter:  1.187 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Unthreaded hole single group  Dc Resistance Rating In Ohms:  5.300 single component single winding  Special Features:  Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	Inductance Type:
25.00 millihenries single component single winding  Body Length: 0.500 inches  Body Outside Diameter: 1.187 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group  Mounting Method: Unthreaded hole single group  Dc Resistance Rating In Ohms: 5.300 single component single winding  Special Features: Case plastic material  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:	Fixed
Body Length:  0.500 inches  Body Outside Diameter:  1.187 inches  Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms:  5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity:  2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Inductance Rating:
O.500 inches  Body Outside Diameter:  1.187 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Unthreaded hole single group  Dc Resistance Rating In Ohms:  5.300 single component single winding  Special Features:  Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	25.00 millihenries single component single winding
Body Outside Diameter:  1.187 inches Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Body Length:
Minding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	0.500 inches
Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Body Outside Diameter:
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	1.187 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Winding Quantity:
Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Dc Resistance Rating In Ohms:  5.300 single component single winding  Special Features: Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:	1 single component
Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Dc Resistance Rating In Ohms: 5.300 single component single winding  Special Features: Case plastic material  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:	Inclosure Type:
1 single group  Mounting Method: Unthreaded hole single group  Dc Resistance Rating In Ohms: 5.300 single component single winding  Special Features: Case plastic material  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:	Fully enclosed
Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Mounting Facility Quantity:
Unthreaded hole single group  Dc Resistance Rating In Ohms: 5.300 single component single winding  Special Features: Case plastic material  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:	1 single group
Dc Resistance Rating In Ohms:  5.300 single component single winding  Special Features:  Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	Mounting Method:
5.300 single component single winding  Special Features:  Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	Unthreaded hole single group
Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Dc Resistance Rating In Ohms:
Case plastic material  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	5.300 single component single winding
Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:	Special Features:
2 tab, solder lug  Shelf Life: N/a Unit Of Measure:	Case plastic material
Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
N/a Unit Of Measure:	2 tab, solder lug
Unit Of Measure:	Shelf Life:
	N/a
Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A058b0	A058b0