NSN 5950-00-458-7484

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-458-7484

| Mounting Hole Diameter: 0.138 inches single group Inductance Type: Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: | |
|---|--|
| Inductance Type: Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Mounting Hole Diameter: |
| Fixed Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 0.138 inches single group |
| Inductance Rating: 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Inductance Type: |
| 25.00 millihenries single component single winding Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Fixed |
| Body Length: 0.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Inductance Rating: |
| O.500 inches Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 25.00 millihenries single component single winding |
| Body Outside Diameter: 1.187 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Body Length: |
| Minding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 0.500 inches |
| Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Body Outside Diameter: |
| 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 1.187 inches |
| Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Winding Quantity: |
| Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 1 single component |
| Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Inclosure Type: |
| 1 single group Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Fully enclosed |
| Mounting Method: Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Mounting Facility Quantity: |
| Unthreaded hole single group Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 1 single group |
| Dc Resistance Rating In Ohms: 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Mounting Method: |
| 5.300 single component single winding Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Unthreaded hole single group |
| Special Features: Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Dc Resistance Rating In Ohms: |
| Case plastic material Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | 5.300 single component single winding |
| Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Special Features: |
| 2 tab, solder lug Shelf Life: N/a Unit Of Measure: | Case plastic material |
| Shelf Life: N/a Unit Of Measure: | Terminal Type And Quantity: |
| N/a Unit Of Measure: | 2 tab, solder lug |
| Unit Of Measure: | Shelf Life: |
| | N/a |
| Demilitarization: | Unit Of Measure: |
| Demilitarization: | |
| | Demilitarization: |
| No | No |
| Fiig: | Fiig: |
| A058b0 | A058b0 |
| | |