

View Online at <https://aerobasegroup.com/nsn/5950-00-459-4047>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.531 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.880 inches

Body Width:

1.250 inches

Body Height:

2.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

35.00 ac volts single component all secondary 200.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0